



Mobil Super™ 1000 15W-40

Mobil Passenger Vehicle Lube , Saudi Arabia

Premium Multigrade Passenger Vehicle Engine Oils

Product Description

Mobil Super™ 1000 15W-40 is a premium quality mineral motor oils. The product is designed to provide protection for your engine under most operating conditions.

Features and Benefits

Mobil Super™ 1000 15W-40 provides engine protection and helps promote long engine life.

- Extended protection against engine wear and deposits formation
- Engine protection during start up
- Helps combat sludge

Applications

Mobil Super™ 1000 15W-40 has been formulated to be suitable for use in vehicles requiring an API SL claim . ExxonMobil particularly recommends Mobil Super™ 1000 for daily driving under normal conditions:

- Passenger cars, SUV's, light trucks and vans (Gasoline engines) requiring an API SL
- Normal Operating Conditions
- Suitable for use under a wide range of temperature conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product meets or exceeds the requirements of:
API SL

Properties and Specifications

Property	
Grade	SAE 15W-40
Viscosity Index, ASTM D2270	134
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	13.7
Flash Point, Cleveland Open Cup, °C, ASTM D92	240
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	102.4
Density @ 15 C, g/ml, ASTM D4052	0.8686
Ash, Sulfated, mass%, ASTM D874	0.7

Property	
Pour Point, °C, ASTM D97	-27
Hi-Temp Hi-Shear Viscosity @ 150 C 1x10(6) sec(-1), mPa.s, ASTM D4683	3.9

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

07-2023

APSCO

Jeddah, Saudi-Arabia

Tel: 00966-2-6081171 / Fax: 00966-2-6370966

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil





© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved