



Mobil Super™ Synthetic 5W-30

Mobil Passenger Vehicle Lube , Saudi Arabia

Synthetic Technology Engine Oil

Product Description

Mobil Super™ Synthetic Technology 5W-30 is a synthetic technology engine oil designed to provide a high level of protection in gasoline vehicles, including the latest generation turbocharged gasoline fuel injected engines found in passenger cars, SUVs, and light commercial vans.

Features and Benefits

Mobil Super™ Synthetic Technology 5W-30 is meticulously engineered for today's tougher engine specifications. It provides very good engine protection to help extend engine life.

- Designed to provide very good wear protection, including timing chain elongation
- Helps to prevent LSPI occurrences in downsized gasoline engines operating under high heavy loads
- Helps to maintain engine cleanliness from sludge and carbon deposits
- Helps fuel economy in regards to ILSAC GF-6A / API Resource Conserving requirements
- Helps ensure compatibility with catalysts used in gasoline emission reduction systems

Applications

Mobil Super™ Synthetic Technology 5W-30 is recommended for use in many types of modern and prior design gasoline powered vehicles from American (Ford, GM, Chrysler...), Japanese (Toyota, Nissan, Mistsubishi, ...) and Korean (Hyundai, Kia, ...) car manufacturers.

Specifications and Approvals

This product has the following approvals:
GM dexos1:GEN3 Licensed
VW VWC 53034
This product is recommended for use in applications requiring:
API CF
This product meets or exceeds the requirements of:
API SN
API SN PLUS
API SP
ILSAC GF-6A
FORD WSS-M2C961-A1

Properties and Specifications

Property	
Grade	SAE 5W-30
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	10.7
Kinematic Viscosity @ 40 C, mm2/s, ASTM D445	61.4
Total Base Number, mgKOH/g, ASTM D2896	7.4
Pour Point, °C, ASTM D97	-42
Cold-Cranking Simulator, Apparent Viscosity @ -30 C, mPa.s, ASTM D5293	4230
Viscosity Index, ASTM D2270	166

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

04-2024

APSCO

Jeddah, Saudi-Arabia

Tel: 00966-2-6081171 / Fax: 00966-2-6370966

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTO
ENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved