



Mobil Super™ 2000 X3 10W-40
Mobil Passenger Vehicle Lube , Saudi Arabia
Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

Mobil Super™ 2000 X3 10W-40 is a semi-synthetic motor oil that provides long engine life and protection against sludge and wear.

Features and Benefits

Mobil Super 2000 products are industry proven, so you can trust your engine will get the protection it needs. Mobil Super 2000 X3 10W-40 gives you confidence in every journey and provides multiple benefits:

- Very good sludge prevention
- Very good engine cleanliness
- Very good high temperature protection
- Very good wear protection
- Very good cold start-up

Applications

ExxonMobil recommends Mobil Super 2000 X3 10W-40 for:

- Older engine technologies
- Gasoline, Ethanol and CNG engines
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop-and-go city driving
- Normal to occasionally severe operating conditions

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

This product is recommended for use in applications requiring:
API CF

This product meets or exceeds the requirements of:
API SJ
API SL
API SM

This product meets or exceeds the requirements of:
API SN

Properties and Specifications

Property	
Grade	SAE 10W-40
Cold-Cranking Simulator, Apparent Viscosity @ -25 C, mPa.s, ASTM D5293	6500
Kinematic Viscosity @ 100 C, mm2/s, ASTM D445	14.5
Pour Point, °C, ASTM D97	-27
Flash Point, °C, ASTM D92	228
Total Base Number, mgKOH/g, ASTM D2896	9.4
Noack Volatility, wt %, CEC L-40-A-94	11.6
Hi-Temp Hi-Shear Viscosity @ 150 C, mPa.s, ASTM D4683	3.8
Viscosity Index, ASTM D2270	155

Health and safety

Health and Safety recommendations for this product can be found on the Material Safety Data Sheet (MSDS) @ <http://www.msds.exxonmobil.com/psims/psims.aspx>

All trademarks used herein are trademarks or registered trademarks of Exxon Mobil Corporation or one of its subsidiaries unless indicated otherwise.

01-2022

APSCO

Jeddah, Saudi-Arabia

Tel: 00966-2-6081171 / Fax: 00966-2-6370966

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

ExxonMobil

Exxon

Mobil

Esso

XTOENERGY

© Copyright 2003-2025 Exxon Mobil Corporation. All Rights Reserved